

Romac CQ6230A Lathe



CQ2630A 910

Max. swing over bed	300 mm
Max. swing over gap	430 mm
Max. length of workpiece	914 mm
Hole through spindle bore	38 mm
Spindle bore taper	Morse No. 5
Spindle speeds (9 steps)	60–1500 rpm
Taper of quill sleeve	Morse No. 3
Metric threads (29 kinds)	0.2–4.5 mm
Inch threads (40 kinds)	4–112 TPI
Longitudinal feed (40 kinds)	0.028–0.791 mm/rev
Cross feed (40 kinds)	0.010–0.268 mm/rev
Max. travel of saddle	800 mm
Max. travel of cross slide	175 mm
Main motor	1.1 kW
Overall dimensions (L x W x H)	1700 x 750 x 1270 mm
Net weight	420 kg



**R O N M A C K
M A C H I N E R Y**

Your leading supplier of specialist metalwork machinery

SHOWROOMS	Perth — Head Office:	T (08) 9445 0700	Metalwork Showroom — 8 Hector Street, Osborne Park, Western Australia 6017		
	Melbourne	T (03) 9933 7777	Unit 1, 38-40 Little Boundary Road, Laverton North, Victoria 3026		
	Queensland	0439 901 646	New South Wales	0422 237 409	South Australia 0439 094 486

We reserve the right to change specifications without notice. Images for illustration purposes.

plasma cutters press brakes guillotines lathes milling machines drills surface grinders CNC machining centres

www.romack.com.au